

DURAEDGEGUARD55 X

Technical Data

Conveyor Accessories (DuraEdgeGuard55 X)

Model: CA-DEGD(X)-NR13055-BLAPP-CD



FOR GENERAL-PURPOSE SEALING

Economical skirting used for material containment in conveyor systems



EASY INSTALLATION ONSITE

Can be cut and fitted on industrial sites



ECONOMICAL AND COST-SAVING

Ideal option for low-to-medium duty conveyor sealing

MEASURED PROPERTIES	TESTING STANDARD	SPECIFIED VALUES	OBSERVED VALUES			
PHYSICAL & MECHANICAL PROPERTIES						
Tensile Strength	ASTM D412	5.0 MPa (Min)	5.2 MPa (Min)			
Elongation at Break	ASTM D412	250% (Min)	272% (Min)			
Hardness	ASTM D2240	45° ± 5° Shore A	46° Shore A			
Specific Gravity	ASTM D297	1.30 ± 0.05	1.31			
Abrasion Loss (mm³)	ASTM D5963	300 mm³ (Max)	280 mm³			
Working Temperature	-	-10 °C to +70 °C	Conforms			

CHEMICAL RESISTANCE					
Ozone	Dilute Acids & Bases	Conc. Acids & Bases	Oils	Solvents	
Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	
IDENTIFICATION					
Colour	Black				
Grade	X				
Polymer	NR/SBR				
Finish	Top & Bottom - Plain				
Packaging	With white coloured HDPE woven fabric				
Labelling	Label indicating Product Name, Dimensions, Batch No., Mfg. Month & Year, Quantity, and Package No. for traceability				

Applications	 Coal handling and power plant sealing systems Aggregate and sand processing conveyors Warehouses with packaged/bagged goods transport Low-speed conveyors in recycling plants Fertilizer unit raw material transfer Cement bagging and dispatch systems Small-scale manufacturing conveyor lines
--------------	--

Note: Manufacturing tolerance of \pm 10% on thickness, \pm 2% on width and length and \pm 10% on weight shall be applicable.







